

Jiffy Tite -12AN Male Plug



Short Description

Jiffy Tite -12AN Male Plug

Description

The Jiffy-tite advantage

Jiffy-tite's revolutionary Quick Connect Fluid Fittings provide unsurpassed performance under extreme racing conditions. Made of lightweight, 6061-T6 aluminum, brass valves, and stainless steel ball bearings, they are corrosion resistant for extra long life.

Jiffy-tite's unique, high-flow valve technology in the plug and socket assembly automatically interrupts the flow of fluid when disconnected to protect against hazardous gas leaks or potential hot oil spills. Tested and proven to have a 100% leak proof seal, even at 200 psi.

Features

- 100% Leak Tested
- Replaces Any Fitting in Any Location
- Available for ALL Fuel, Oil, and Water Applications
- Will not wear out
- Avoids stripping, cross-threading and over-tightening
- Maximum Operating Pressure: 200 PSI
- Operating Temperature: -40° to 350° F; -40° to 177° C
- Works with most steel-braided, lightweight black and push-to-lock hose styles except Teflon®.

- For pump gas, race gas, E85 and alcohol applications, Buna N (Nitrile) seals are recommended
- For Methanol and Nitromethane applications, EPDM seals are recommended
- Jiffy-tite fittings permit fluid to flow in both directions