

# Speedflow Hoses - 400 Series



## Short Description

Speedflow's 400series hose is designed specifically for 400 series pushlock style fittings.

## Description

Size	Part No (blue)	Part No (Black)	Inside Diameter	Outside Diameter	Operating Pressure	Burst Pressure	Bend Radius
-4	400-04	400-04p	0.250in / 6.35mm	0.500in / 12.70mm	250psi / 17bar	1000psi / 69bar	3.00in / 76.20mm
-6	400-06	400-06p	0.375in / 9.53mm	0.620in / 15.75mm	250psi / 17bar	1000psi / 69bar	3.00in / 76.20mm
-8	400-08	400-08p	0.500in / 12.70mm	0.750in / 19.05mm	250psi / 17bar	1000psi / 69bar	5.00in / 127.00mm
-10	400-10	400-10p	0.625in / 15.88mm	0.900in / 22.86mm	250psi / 17bar	1000psi / 69bar	6.00in / 152.40mm
-12	400-12	400-12p	0.750in / 19.05mm	1.030in / 26.16mm	250psi / 17bar	1000psi / 69bar	7.00in / 177.80mm

Speedflow's 400series hose is designed specifically for 400 series pushlock style fittings. This hose has an elastomer tube with a smooth outer cover. This is not recommended for use with unleaded fuels or use in high pressure applications or suction systems. This hose is suitable for use with synthetic lubricants, oils, air, coolant and methanol.

Temperature Range: -46°C (-50.8°F) to 150°C (302°F).