

# Speedflow Hoses - 100 Series



## Description

Size	Part No	Inside Diameter	Outside Diameter	Operating Pressure	Burst Pressure	Bend Radius
-4	100-04	0.219in / 5.56mm	0.438in / 11.13mm	1000psi / 69bar	6000psi / 420bar	2.00in / 50.80mm
-6	100-06	0.344in / 8.73mm	0.547in / 13.89mm	1000psi / 69bar	6000psi / 420bar	2.50in / 63.50mm
-8	100-08	0.438in / 11.12mm	0.641in / 16.28mm	1000psi / 69bar	5000psi / 350bar	3.50in / 88.90mm
-10	100-10	0.562in / 14.27mm	0.797in / 20.24mm	1000psi / 69bar	5000psi / 350bar	4.00in / 101.60mm
-12	100-12	0.688in / 17.47mm	0.928in / 23.82mm	1000psi / 69bar	3750psi / 263bar	4.50in / 114.30mm
-16	100-16	0.875in / 22.22mm	1.156in / 29.36mm	750psi / 52bar	2500psi / 175bar	5.50in / 139.70mm
-20	100-20	1.125in / 28.70mm	1.437in / 36.49mm	500psi / 35bar	2000psi / 138bar	8.00in / 203.30mm

Speedflow 100 series hose is the premier stainless steel nitrile hose. Manufactured in the USA specifically for Speedflow Products, this hose has been used by motorsport professionals all over the world! Designed for use with the wide variety of 100 series hose ends to provide essential protection and resistance to high pressure, temperature and chafing. It is constructed of a seamless synthetic nitrile inner tube with an integral stainless steel braid and a high tensile stainless steel outer braid. Speedflows 100 series hose has the highest corrosion and fire resistance of any other nitrile braided hose on the market.

Temperature range: -46°C (-50.8°F) to 150°C (302°F).

Give us a call on 09 525 6858 to find out price and availability.