

## Speedflow Hoses - 200 Series



### Short Description

Also available in Black

### Description

Size	Part No	Inside Diameter	Outside Diameter	Operating Pressure	Burst Pressure	Bend Radius
-3	200-03	0.125in / 3.18mm	0.250in / 6.35mm	4250psi / 290bar	12750psi / 870bar	1.50in / 38.10mm
-4	200-04	0.188in / 4.78mm	0.312in / 7.92mm	4110psi / 280bar	12350psi / 840bar	2.00in / 50.80mm
-6	200-06	0.313in / 7.95mm	0.466in / 11.84mm	3380psi / 230bar	10140psi / 230bar	4.00in / 101.60mm
-8	200-08	0.415in / 10.54mm	0.526in / 13.35mm	2790psi / 190bar	8380psi / 570bar	5.25in / 133.40mm
-10	200-10	0.535in / 13.60mm	0.655in / 16.64mm	2200psi / 150bar	6610psi / 450bar	8.00in / 203.30mm

Speedflow 200 Series Teflon Braided hose is constructed from a PTFE inner tube compatible with all brake & clutch fluids, oil & fuels. The outer stainless steel braided covers adds fire and heat resistance and gives the hose a high pressure rating. Sizes -6 and up are manufactured with an anti-static PTFE tube suitable for use as main fuel lines. 200 Series hose has been an industry standard since the mid 60's when it was first used as brake lines to reduce expansion and provide a much firmer "pedal" and more consistent braking. Since then this hose has evolved to be recommended in clutch, pressure lines, turbo lines and fuel systems.

Temperature range: -70°C (-94°F) to 260°C (500°F).

### **Product Gallery**

